



FOR ACCEPTANCE	
DATE	NAME
11/04/06	CARLES (HOUIN)
SIGNATURE	

CIRCUIT	P	0	
1-2	■	■	120°/300°
1-3	■	■	
4-5	■	■	
4-5	■	■	

CHARACTERISTICS

ELECTRICAL CHARACTERISTICS

standard switch : DCE 24
 Rated amperage : 15(A) A
 Rated voltage : 250V
 Type of current : Vcc
 Switch configuration: DPDT
 Switch for appliance classe II
 Number of electrical operations : 10 000
 connections terminal : 6.35 x 0.8

MECHANICAL CHARACTERISTICS

Winding torque : 1.5 TO 4.5 Kgcm
 Return torque to zero position: 1 TO 4.5 Kgcm

timing : 120°
 timing range : ±5%

Residual operating torque : 0.1 daN.cm
 Torque of manual position : 4 Kg.cm

THERMAL CHARACTERISTICS

Maximum temperature of use : 125° C

MARKING ON BACK CASE

Type M12
 T= 125°C
 identification of terminals

APPROVALS

UL- SEWKO- ENEC10- VDE- CSA- IMQ
 16A 250V AC RESISTIVE
 4A 250V AC INDUCTIVE

MARKING

Label of the timer : 4 numbers
 week of production : 2 numbers
 Year of production : 2 numbers

CUSTOMER : PIRIS	WEIGHT BY 1000	USE: /
CUSTOMER PART NUMBER :	COLOR: BLACK	SETS M2
M12/120/300/336/18800A/P36/M1000/23/22.5/6.0M4.6	2678	C
DRAWN BY : MARTINET.C	DATE: 11/04/06	SCALE: 1/1
FAUCIGNY INSTRUMENTS		

DA06055