



CHARACTERISTICS

ELECTRICAL CHARACTERISTICS

standard switch : CEE 24
 Rated amperage : 16(4) A
 Rated voltage : 250V
 Type of current : Vac
 Switch configuration: DPDT
 Switch for appliance classe II
 Number of electrical operations : 10 000
 connections terminal : 6.35 x 0.8

MECHANICAL CHARACTERISTICS

Winding torque : 1.5 TO 4.5 Kgcm
 Return torque to zero position: 1 TO 4.5 Kgcm
 timing : 60'
 timing range : ±5%
 Residual operating torque : 0.1 daN.cm
 Torque of manual position : 4 Kg.cm

THERMAL CHARACTERISTICS

Maximum temperature of use : 125° C

MARKING ON BACK CASE

Type MI2
 T= 125°C
 Identification of terminals

APPROVALS

UL- SEMKO- ENEC10 VDE- CSA- IMQ
 16A 250V AC RESISTIVE
 4A 250V AC INDUCTIVE

MARKING

Label of the timer : 4 numbers
 week of production : 2 numbers
 Year of production : 2 numbers

DP271108

| | | |
|--|----------------|------------|
| CUSTOMER : PIRIS | WEIGHT BY 1000 | USE: / |
| CUSTOMER PART NUMBER : / | COLOR: BLACK | SETS MI2 |
| MI2/60/300/336/18800A/P36/AM000/23/22.5/6.0MT4.6 | 2730 | B |
| DRAWN BY : MARTINET.C | DATE: 27/11/08 | SCALE: 1/1 |
| FAUCIGNY INSTRUMENTS | | |