

**Model: THG1340YKS**
**Product Description**

**Type:** Reciprocating  
**Application:** LBP - Low Back Pressure  
**Refrigerant:** R-134a  
**Voltage/Frequency:** 220-240V ~ 50Hz  
**Version:** N/A

**Product Specifications**
**Performance**

Condition	Test Voltage	Refrigeration Capacity			Input Power	Efficiency			EVAP TEMP	COND TEMP	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		Btu/h	kcal/h	W	W	Btu/Wh	kcal/Wh	W/W					
CECOMAF	220V ~ 50HZ	260	66	76	75	3.47	.87	1.02	-25°C (-13°F)	55°C (131°F)	32°C (90°F)	32°C (90°F)	55°C (131°F)
ASHRAE	220V ~ 50HZ	355	89	104	80	4.44	1.12	1.3	-23°C (-10°F)	54°C (130°F)	32°C (90°F)	32°C (90°F)	32°C (90°F)

**General**

**Evaporating Temp. Range:** -34.4°C to -12.2°C (-30°F to 10°F)  
**Motor Torque:** Low Start Torque (LST)  
**Compressor Cooling:** Static

**Mechanical**

**Weight:** 8  
**Weight Unit of Measure:** KG  
**Displacement (cc):** 3.79  
**Oil Type:** Polyolester  
**Viscosity (cSt):** 10  
**Oil Charge (cc):** 243

**Electrical**

**Voltage Range (50 Hz):** 198-253  
**Voltage Range (60 Hz):** N/A  
**Locked Rotor Amps (LRA):** 8.5  
**Rated Load Amps (RLA 50 Hz):** .62  
**Rated Load Amps (RLA 60 Hz):** 0  
**Max. Continuous Current (MCC in Amps):** 0  
**Motor Resistance (Ohm) - Main:** 23.51  
**Motor Resistance (Ohm) - Start:** 29.41  
**Motor Type:** PTCS\_IR  
**Overload Type:** N/A  
**Relay Type:** N/A

**Agency Approval**

CE Listed, GOST RUSSIA Listed, VDE Listed